

als

RTV
GASKET MAKER
RED

• 100% SILICONE RUBBER
• PERMANENTLY FLEXIBLE
• WITHSTANDS -60°F TO 600°F
• INSTANTLY FORMS ANY SIZE
OR SHAPE OF GASKET

Product # 1119

For Professional Use Only

RTV Adhesive/Sealant will bond, caulk, seal, fasten, insulate, protect and repair many types of materials. Because it is virtually unaffected by weather, temperature extremes, chemicals and aging, it offers unmatched performance even under the most severe operating conditions. This material also seals or replaces a wide range of cork, paper, asbestos, felt and metal gaskets. **RTV** works on flanges, cover plates, hose connections and threaded assemblies.

DIRECTIONS FOR USE:

1. Remove old gaskets, all oil and grease, then dry the surface.
2. Apply fingertip pressure to valve stem and lay a thin, even bead (1/16" to 1/8"), to one mating surface, encircling all bolt holes.
3. Allow bead to "skin" (approx. 15 minutes) before assembling parts.
4. Assemble carefully and do not over-tighten bolts.
5. If tooling is required, complete within 5 minutes. Remove excess sealant immediately with dry paper towel or knife.

Paintability: Most paints do not adhere well to this sealant. Complete painting before applying.

Oily woods: This product does not adhere well to oily woods such as cedar, teak and cypress.

Do not use on: Intake/exhaust manifolds, head gaskets, carburetor base gaskets.

1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
	PROTECTION


INGREDIENTS	CAS NUMBER
SILICA, AMORPHOUS	7631-86-9
METHYLTRIACTOXY-SILANE	4253-34-3
ETHYLTRIACTOXY-SILANE	17689-77-9
POLYDIMETHYLSILOXANE	63148-62-9
POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED	70131-67-8

Additional Information

RTV Silicone Adhesive/Sealant is the fastest and easiest way to replace gaskets and seal joints of all kinds. With **RTV Gasket Maker** there is no need to keep hundreds of different gaskets in stock or spend extra time cutting out gaskets from sheets of cork. This remarkable product instantly forms any size gasket and stays permanently flexible providing the ultimate in durability and performance. Use **RTV** instead of plumber's putty and eliminate the leaks cause by slightly loose fixtures breaking the seal provided by putty alone. **RTV** is much faster and easier than Teflon tape and will generally provide a much longer lasting seal. Use on; oil pans, water pumps, valve axle covers, weather-stripping, cam shaft covers, thermostat housings, push rod covers, transmission pans, pipe fittings, hose connections, etc. **RTV** comes packaged in a unique charged-piston can that dispenses a consistent bead without the need of a caulking gun. Use **RTV** in any situation where other adhesive/sealants have failed or a replacement gasket is not readily available.

STORAGE INSTRUCTIONS

Leave a small bead of material which will form a sealing "plug" for reuse. To reuse, gently pull out "plug" and begin to use material. If plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.



Corporate Office
Burbank, California
To Order Call (800) 366-0961



NATIONWIDE DISTRIBUTION
• Burbank • Atlanta
• Philadelphia • Houston